

GO GO[®] ULTRA X

3 & 4-WHEEL SCOOTER

ECONOMY
CLASS PRICE,
FIRST CLASS
FEATURES

The **Go-Go[®] Ultra X** is loaded with features such as one-hand disassembly and a convenient drop-in battery box for worry-free travel. With a 260 lb. weight capacity, a maximum speed up to 4 mph, speeds up to 6.9 mph on the 3 wheel and 7.2 miles on the 4-wheel makes it an exceptional value.



Go-Go[®] Ultra X 3-wheel



Go-Go[®] Ultra X 4-wheel



Feather-touch disassembly

 facebook.com/PrideMobilityProductsCorp


 youtube.com/PrideMobility

PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]

pridemobility.com

SPECIFICATIONS

GO-GO® ULTRA X 3W: SC40X 4W: SC44X

Weight capacity:	260 lbs.
Maximum speed ¹ :	Up to 4 mph
Ground clearance ² :	2.25" at mid-frame, 1.25" at motor
Turning radius ² :	3W: 33" 4W: 44"
Overall length ² :	3W: 37" 4W: 39.5"
Overall width ² :	19.5"
Front tires:	3W: 2" x 8" solid 4W: 2" x 7" solid
Rear tires:	2.5" x 8" solid
Range per charge ^{1,4} :	3W: 6.9 miles 4W: 7.2 miles
Total weight without batteries ⁴ :	3W: 76 lbs. 4W: 80 lbs.
Heaviest piece when disassembled:	3W: 29.5 lbs. (front section) 4W: 34 lbs. (front section)
Standard seating:	Type: Foldable, compact, vinyl-covered molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17", Depth: 17"
Motor output:	24-volt DC motor, sealed mini-transaxle
Brakes:	Regenerative and electromechanical
Battery requirements ^{2,3} :	(2) 12V deep-cycle Size: (2) 12 AH Weight: 9 lbs. each, 20 lbs. per battery pack
Battery charger:	Off-board, 2 amp
Color:	 Red

FEATURES

- Feather-touch disassembly permits simple frame separation with only one hand
- Pride's exclusive black, non-scuffing tires
- Auto-connecting front-to-rear cable
- Front frame-mounted seat post offers maximum stability
- Frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
- Modular design for easy serviceability
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board

Pride Lifts & Ramps

Compatible Lifts:

- Backpacker® Plus
- Outlander Full Platform
- Backpacker® AVP
- Outlander TM
- Olympian



¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ This range was obtained with the 4-wheel model.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

(US) 800-800-8586 • (Canada) 888-570-1113

pridemobility.com