

# CONSUL Two post lifts - Limited & Classic series



Cable bridge, overhead fitting as standard can be recessed into workshop if required.

## Equipment

The Limited and Classic series two-post lifts from Consul are fully baseless with lifting capacities of 3000 - 4000kgs. They are manufactured to the highest standards and include full safety systems for the Load Nut and arm locking systems. Fully CE Approved.

- Electronically synchronised columns made of hot-rolled profile steel
- Columns turned by 30° (improved angle for door opening)
- Short swivel arms movable from both sides (for 3.000 kg version)
- Bronze alloy load nut / cast alloy safety nut
- Oil dispenser for supporting lubrication (Classic)
- Carriage with 6 maintenance-free roller bearings (Limited, 4 rollers)
- Broken nut raise lock-down feature
- Covering of post interior
- Acoustic foot protection
- Cushioning door stop, adjustable pick up plate (approx. 25 mm)
- Lockable operating device with reversing contactor
- Automatic arm locking device with manual release function
- Protection class IP54, GS-approved, DIN EN 1493, CE-certificate



Option of various height lift pads



**Multitune GE Ltd**  
25 The Avenue  
Wroxham  
Norwich  
NR12 8TR

Telephone : 01603 781999  
email : [multituneltd@gmail.com](mailto:multituneltd@gmail.com)  
Website : [www.multitune.net](http://www.multitune.net)

Made mitten in Germany



Model		2.30 Limited	2.30 Classic	2.40 Classic
Nr.		48400.6	54080.7	54090.6
Capacity	kg	3.000	3.000	4.000
Motor data	kW / A / V	2 x 2,5 / 20 / 400	2 x 2,5 / 20 / 400	2 x 2,5 / 20 / 400
Lifting- / lowering time	secs	50	50	50
A *Lifting height	mm	2.005	2.005	2.010
B Height to top of post Height to top of bridge	mm	2.550 4.030	2.550 4.030	2.550 4.030
C Set-up width	mm	3.315	3.444	3.444
D Drive-through width	mm	2.320	2.320	2.320
E Long arm extension min.	mm	830 (2 pieces)	830 (2 pieces)	760 (3 pieces)
F Long arm extension max.	mm	1.330 (2 pieces)	1.330 (2 pieces)	1.460 (3 pieces)
G Short arm extension min.	mm	560 (2 pieces)	420 (3 pieces)	760 (3 pieces)
H Short arm extension max.	mm	760 (2 pieces)	830 (3 pieces)	1.460 (3 pieces)
I ** Lift Pad lowest point	mm	85	85	90
J Clear distance, between columns	mm	2.650	2.650	2.650

\* Lifting heights only reachable with optional accessories

\*\* Lowest lift pad heights reachable with optimal floor conditions

