



AFRICA 2000

PRODUCT DESCRIPTION

An acrylic emulsion based paint, formulated to provide good performance at an economical price.

PRODUCT FEATURES

AFRICA 2000 was developed to meet the need for a low cost coating, which makes it ideally suited to improving the image of low cost housing, farm boundary walls & other unsightly buildings. AFRICA 2000 is a better option for walls which would normally be painted with white wash.

TECHNICAL INFORMATION

Colour: White & cream
Appearance: Matt finish
S.G.: ±1.25
Viscosity: ±89 KU
Spreading rate: 3 - 5m²/litre depending on surface porosity
Solvent: Water
Packaging: 5 & 20 litres

SURFACE PREPARATION

All surfaces are to be clean, dry & free of oil, grease, dirt & old flaking paint. Should the substrates be powdery or weak, it is recommended to remove as much as possible of the loose powdery surface. Then seal with at least 1 coat of Acrylic Sealer. Allow to dry for 12 hours at 25°C prior to painting with AFRICA 2000.

APPLICATION

Stir contents thoroughly. Use as supplied, do not dilute. 2 Coats recommended. Apply by brush & roller, as supplied. clean up with water. Do not allow to dry on equipment.

ENVIRONMENT

It is recommended that application be confined to the following:

Surface temperature: Min. 15°C Max. 40°C

Ambient temperature: Min. 15°C Max. 40°C

Relative humidity: Min.0% Max.85%

Or at least 3°C above Dew point

Do not leave container open, as skin forms on the surface of the paint.

DRYING TIME

Substrate Temp	Touch Dry	Hard Dry
15°C	2½ hours	18 hours
20°C	1¼ hours	12 hours
25°C	45 minutes	10 hours
30°C	30 minutes	4 hours

OVERCOATING TIMES

15°C: 18 hours

20°C: 12 hours

25°C: 10 hours

30°C: 8 hours

LIMITATIONS

At no time should painting be done in inclement weather or before 9am & after 2pm in winter. Avoid wet weather & wet substrates.

SAFETY PRECAUTIONS

No known problems resulting from contact with skin, however, remove as soon as possible with soap and water. Avoid ingestion and contact with eyes. If ingested, seek medical attention. Do not induce vomiting. If paint contact is made with eyes, rinse eyes well with water & seek medical attention. Do not smoke when painting. Ensure good ventilation during painting and drying.

KEEPOUTOFREACHOFCHILDREN.

Information Provided is based on Laboratory evaluations and data believed to be reliable.

Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for their own use. It is not to be considered a guarantee of the products properties.

For more information contact our Factories:

Western Cape: Tel/Fax: (021) 853-8105 Mpumalanga: Tel: (013) 246-2570 Fax: (013) 246-2573