



## ECOCOAT

### PRODUCT DESCRIPTION

An Acrylic co-polymer based paint, formulated to provide performance at a economical price.

### PRODUCT FEATURES

ECOCOAT was developed to meet the needs for economic cost application requirements.

ECOCOAT is suitable for interior ceilings and walls.

ECOCOAT can be applied outside.

### TECHNICAL INFORMATION

Colour: White, Cream and Peach Haze.  
Appearance: Matt  
Generic type: Acrylic co-polymer  
Total solids: 40%  
S.G.: 1.28  
Viscosity: 108 Ku  
Spreading rate: 6 - 8 m<sup>2</sup>/ litre.  
Solvent: Water  
Artificial weathering: Fair  
Opacity: Translucent when dry.

### SURFACE PREPARATION

All surfaces are to be clean, dry, free of dirt, oil, grease and old flaking paint.

Should the substrate be powdery or weak, it is recommended to remove as much as possible of the loose powdery surface.

Then apply at least one coat of Acrylic Sealer.

Allow to dry for at least 4 hours prior to painting with ECOCOAT.

### APPLICATION

Stir contents thoroughly, use as supplied. Do not dilute. 3 Coats of 50µ each are recommended for optimum results.

Brush and Roller: Suitable as supplied. Do not dilute.

Clean up: Wash with water, do not allow product to dry on in equipment

### ENVIRONMENT

It is recommended that application be confined to the following:

Surface temperature: 40 degrees C

Ambient temperature: 40 degrees c

Relative humidity: 80 %

Do not leave the container open, as a skin will form on the surface of the paint.

### DRYING TIME

Substrate Temp	Touch Dry	Hard Dry
15° C	4 Hours	8 hours
20° C	3Hours	6 hours
25° C	2 hour	4 hours

Information Provided is based on Laboratory evaluations and data believed to be reliable.  
Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for their own use.  
It is not to be considered a guarantee of the products properties.

For more information contact our Factories:  
Western Cape: Tel/Fax: (021) 853-8105 Mpumalanga: Tel: (013) 246-2570 Fax: (013) 246-2573



30°C	45 minutes	4 hours
------	------------	---------

**OVERCOATING TIMES**

15°C: 6 hours  
20°C: 4 hours  
25°C: 2 hours  
30°C: 1 hours

**LIMITATIONS**

Sustained cold conditions can result in paint failure.  
Avoid painting on wet substrates and in wet conditions  
At no time should painting be done in inclement weather or before 9 am and after 3 pm in winter.

**STORAGE AND HANDLING**

Store in a cool and dry area, away from heat, direct sunlight and severe cold.  
Shelf Life: 2 years in original sealed containers.

**SAFETY PRECAUTIONS**

No known problems resulting from contact with skin.  
Remove however as soon as possible with soap and water.  
Avoid ingestion and contact with eyes. If ingested seek Medical attention. Do not induce vomiting.  
If paint contact is made with eyes, rinse eyes well with water and seek medical attention.  
Do not smoke when painting.  
Ensure good ventilation during painting.

KEEP OUT OF REACH OF CHILDREN.

Information Provided is based on Laboratory evaluations and data believed to be reliable.  
Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for their own use.  
It is not to be considered a guarantee of the products properties.

For more information contact our Factories:  
**Western Cape:** Tel/Fax: (021) 853-8105 **Mpumalanga:** Tel: (013) 246-2570 Fax: (013) 246-2573